

CLAIMS:

- 5 1. A juvenile vehicle seat comprising
a base and
a cup holder,
the cup holder having a retracted position adjacent the base and an
extended position spaced from the base.
- 10 2. The juvenile vehicle seat of claim 1, wherein the cup holder is
carried by a connecting member, the connecting member being movable relative to
the base.
3. The juvenile vehicle seat of claim 1, wherein the cup holder is
slidably mounted to the base.
- 15 4. The juvenile vehicle seat of claim 2, wherein the base provides
a receptor for the connecting member.
5. The juvenile vehicle seat of claim 2 further comprising a detent
carried on one of the base or the connecting member and a notch provided in the other
of the base or the connecting member to inhibit movement of the cup holder from at
least one of the retracted or extended positions.
- 20 6. The juvenile vehicle seat of claim 2, wherein the connecting
member includes a detent, the base includes a notch, and the detent engages the notch
to inhibit movement of the cup holder from the extended position toward the retracted
position.
- 25 7. The juvenile vehicle seat of claim 6, wherein the base further
includes an opening and the detent engages an edge of the opening to inhibit
movement of the cup holder from the retracted position toward the extended position.
8. The juvenile vehicle seat of claim 7, wherein the connecting
member further includes a catch that engages the edge of the opening to inhibit
removal of the cup holder from the base.
- 30 9. A juvenile seat assembly comprising:
a juvenile vehicle seat, and

09331503 "051401"

a cup holder movably secured to the juvenile vehicle seat, the cup holder being positionable between a first position and a second position,

wherein the cup holder is spaced apart from the juvenile vehicle seat by a first distance when the cup holder is in the first position and is spaced apart from the juvenile vehicle seat by a second distance when the cup holder is in the second position, the first distance being less than the second distance.

10. The assembly of claim 9, wherein the cup holder includes a cylindrically-shaped cup retainer defined therein.

11. The assembly of claim 9, wherein the cup holder is slidably secured to the juvenile seat.

12. The assembly of claim 9, wherein the assembly further comprises a base, the seat being removably secured to the base, and the cup holder is movably secured to the base.

13. The assembly of claim 12, wherein the base is formed to include an aperture defined therein, and the cup holder includes a connector, the connector extending into the aperture.

14. The assembly of claim 13, wherein the connector includes a first portion and the base includes a second portion, the first portion cooperating with the second portion to inhibit movement of the cup holder from at least one of the first or second positions.

15. The assembly of claim 14, wherein the first portion includes a detent and the second portion provides an engagement edge, the detent engaging the edge when the cup holder is in the first position to inhibit movement of the cup holder from the first position toward the second position.

16. The assembly of claim 15, wherein the first portion further includes a catch that engages the edge when the cup holder is in the second position to inhibit removal of the cup holder from the base.

17. The assembly of claim 15, wherein the second portion includes a notch and the detent engages the notch when the cup holder is in the second position to inhibit removal of the cup holder from the base and to inhibit movement of the cup holder from the second position toward the first position.

18. A juvenile vehicle seat comprising

05831503 "061401

a cup holder coupled to the seat and movable relative to the seat between a retracted position proximate the seat and an extended position spaced apart from the seat,

the cup holder having a connecting member engaging the seat to
5 inhibit movement of the cup holder from at least one of the retracted and extended positions.

19. The juvenile vehicle seat of claim 18, wherein the connecting member includes a retainer and the seat includes a first retainer engaging portion and a second retainer engaging portion, wherein the retainer engages the first retainer
10 engaging portion to inhibit movement of the cup holder from the extended position and the retainer engages the second retainer engaging portion to inhibit movement of the cup holder from the retracted position.

20. The juvenile vehicle seat of claim 18, wherein the connecting member includes a first retainer and a second retainer and the seat includes a retainer
15 engaging portion, wherein the first retainer engages the retainer engaging portion to inhibit movement of the cup holder from the retracted position and the second retainer engages the retainer engaging portion to inhibit movement of the cup holder from the seat.

20

25

30